

Product Specification

Product information	Product Category	LED Point Light		
	Product Type	PP0003-LED0.9M-RGB	PP0003-LED1.5M-RGB	PP0003-LED1.8M-4080
	Appearance			
	Dimension	85x94.5mm		
	Weight	0.25Kg		
Module	Input Current	0.13A	0.21A	0.21A
	Input Voltages	DC24V		
	Installation	Surface mounted		
	Power	0.9W	1.5W	1.8W
	Quantity of LEDs	4 pcs	6 pcs	6 pcs
	Lumens output	30.6	51	60.5
	Luminous efficiency	34.0	34.0	33.6
	Color temperature	RGB	RGB	RGBW4000K
	Beam Angles	≥95°		
	CRI	/	/	/
	IP	IP66	IP66	IP66
	IK	IK08	IK08	IK08
	Optics	/	/	/
	Type of protection	ClassIII		
Chip information	Recommended model 1	LUMILEDS & CREE	LUMILEDS & CREE	LUMILEDS & CREE
	Recommended model 2	/	/	/
Driver information	output power of driver	/	/	/
	Isolation driver	/	/	/
	Dimmable	DMX512	DMX512	DMX512
	Installation	Remove	Remove	Remove
	Recommended model 1	Mean Well	Mean Well	Mean Well
	Recommended model 2	/	/	/
Environment and safety	Application Temperature	-20°C to 50°C	-20°C to 50°C	-20°C to 50°C
	Application THumidity	/	/	/
	Wind speed	/	/	/
	Windward area	/	/	/
	Thunder-resistant	/	/	/
	Shock-resistant	/	/	/
Certification	LM80	Y	Y	Y
	CE of driver	/	/	/
	CE of light	Y	Y	Y
	UL of light	/	/	/
	ROHS of light	Y	Y	Y
	Executive standard	EN60598-1		
Life Time	L80/B50 50000H			